



# BJM Submersible Pump - Floating

KSW Oilfield Rental  
Corporate Office:  
6931 S. 66th E. Ave.  
Suite 105  
Tulsa, OK 74113  
918.933.6857

[www.dupre.com/kswoilfield](http://www.dupre.com/kswoilfield)

## Key Features

- Designed to tackle the toughest jobs
- Perfect solution for sand, sludge, and slurry removal
- Heavy duty submersible
- Agitator to fluidize settled solids into slurry
- Semi-open impeller to handle abrasive solid concentrations, as high as 70% by weight
- Top discharge
- Dual set-up mounted in float
- Re-circulate water from working pits
- Wash off shaker slides and centrifuge slides

## Float

- Solid polypropylene
- 44" x 48"
- Reinforced eye handles for easy lifting

## BJM Submersible Pump \*

(\*Based on specific gravity of 1.0)

- HP 7.5
- Volt 220/480
- RPM 1750
- Amps 9.5
- Discharge connection 4" NPT-M
- Max solids 1"
- Max head 57'
- Max GPM 594
- 3 Phase
- Weight 375 lbs

## Control Panel

- Manual motor starter
- HP 10
- Volt 600
- Explosion proof
- Toggle or push button switch
- Cast aluminum enclosure

