



Diesel Transfer Pump

KSW Oilfield Rental
Corporate Office:
6931 S. 66th E. Ave.
Suite 105
Tulsa, OK 74113
918.933.6857

www.dupre.com/kswoilfield

Key Features

- Oil base mud mixing
- Designed to handle heavier mud with 40 HP engine
- Handles up to 3" solids
- Advance design maintenance features
- Air cooled engine
- Low exhaust emission meets exhaust regulations
- Forklift slots for easy maneuvering
- Heavy duty .25" steel cage and skid
- Diesel tank made of heavy gauge steel
- 2.8 gallons of diesel per hour at full load (80 gallon tank)
- Sturdy lifting eyes

Centrifugal Pump *

(*based on specific gravity of 1.0)

Super T Series: Self Priming Engine Driven

- 4"
- PSI 70
- GPM 800
- Max head 130'
- Max solids 3"
- 1" Free drain valve
- Cast iron with hardened impeller wear plate



Duetz Diesel Engine

- D914L03
- HP 58
- Advanced injection and combustion system
- Oil cooler flow thermostatically controlled on engine with heating system
- Operating RPM 2,300
- 3 Cylinders
- Grey cast iron
- Electric starting system
- Three ring piston, two compression rings, and one oil scraper ring

?????

- 6"
- GPM 1,630
- PSI 75
- Max head 140
- Max solids 3"
- 1" freeze drain valve
- Cast iron with hardened impeller wear plate