



Generator

KSW Oilfield Rental
Corporate Office:
6931 S. 66th E. Ave.
Suite 105
Tulsa, OK 74113
918.933.6857

www.dupre.com/kswoilfield

Key Features

- Reliable 3 phase power in a highly mobile package
- Oil pressure warning and shutdown
- Coolant temperature warning and shutdown
- -40° F to 185° F operating temperature range
- Emergency stop switch located on outside of enclosure
- Fuel tank is an integral part of the generator skid
- 147 gallon fuel capacity with minimum 24 hour full load run time
- Turbocharged diesel engine while maximizing fuel efficiency

Generator

- 3 Phase KW Standby 63
- 3 Phase KW Prime 58
- 3 Phase Amps 480 Volt
- 1 Phase KW Standby 56
- 1 Phase KW Prime 52
- 1 Phase Amps 240 Volt
- AC Voltage 1 Phase 120,139,208,220,240,277
- AC Voltage 3 Phase 208,220,440,480
- Frequency HZ 60
- Power Factor 1.0 (1 Phase) .8 (3 Phase)
- Sound DBA 23 ft. @ prime

Engine

- John Deere Tier III
- Aspiration Turbo
- Power-Prime @ 1800 RPM HP 91
- Displacement cubic in (L) 274
- Cylinders 4
- RPM Speed 1800
- Fuel consumption – prime gph (Lph) 5.6

